Installation Manual

Mini Spray Dryer S-300 in open suction mode

Reading and following the instructions in this document does not replace reading and following the instructions in the operation manual.


Close the easy clamp.



Configuration

The following instruments are necessary for the open suction mode:

- Mini Spray Dryer S-300
- Dehumidifier S-396 (optional)



Dehumidifier S-396

1 Inlet 2 Outlet

Mini Spray Dryer S-300

3 Outlet

- 4 Inlet
- 5 Aspirator right
- 6 Aspirator left
- 7 Heater

- 8 Filter pressure **OUT**
- 9 Filter pressure IN

Securing the tubes

► Attach the tubing pieces.




Tighten the nut.



Installing the open suction mode

Precondition:


- ☑ The mini spray dryer is prepared. See operation manual "Mini Spray Dryer S-300".
- ☑ The dehumidifier is prepared. See operation manual "Dehumidifier S-396".
- ☐ The tubing inside the Mini Spray Dryer S-300 is installed. See installation manual "Mini Spray Dryer S-300 in open pressure mode " or "Mini Spray Dryer S-300 in open suction mode ".
- ► Install the process gas tube to the dehumidifier OUT.
- ▶ Install the other end from the tube to the Mini Spray Dryer S-300 inlet.
- ➤ Secure the process gas tube with the easy clamp.
- ► Install the process gas tube inside of the Mini Spray Dryer S-300 to the inlet.
- ► Install the other end from the tube to the heater.
- Secure the process gas tube with the easy clamp.








► Install the angle tube to the filter.



- ► Install the process gas tube to the filter pressure OUT.
- ► Install the other end from the tube to the filter pressure IN.

 See operation manual "Mini Spray Dryer S-300".



- ➤ Secure the process gas tube with the easy clamp.
- ► Install the filter sensors. See operation manual "Mini Spray Dryer S-300".
- Install the process gas tube inside of the Mini Spray Dryer S-300 to the filter pressure IN.
- ► Install the other end from the tube to the aspirator **right**.
- ➤ Secure the process gas tube with the easy clamp.
- ▶ Install the process gas tube inside the Mini Spray Dryer S-300 to the aspirator left.
- ► Install the other end from the tube to the Mini Spray Dryer S-300 outlet.
- ➤ Secure the process gas tube with the easy clamp.

