

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

*** SECTION 1: Identification of the substance/mixture and of the company/undertaking**

*** 1.1 Product identifier**

Trade name/designation R 449A
Art-Nr(n). 0092, 0092A, 0092R

1.2 Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture
Refrigerant

1.3 Details of the supplier of the safety data sheet

Supplier
GHC Gerling, Holz & Co. Handels GmbH
Ruhrstraße 113
D-22761 Hamburg
Telephone +49 40 853 123 0
E-mail hamburg@ghc.de
Website www.ghc.com

Department responsible for information:
GHC Gerling, Holz & Co. Handels GmbH
Telephone +49 40 853 123 0

E-mail (competent person):
msds@ghc.de

1.4 Emergency telephone number

EN: Poison Information Center Mainz +49 6131 19240

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 [CLP] Classification procedure

Press. Gas (Liq.), H280

Hazard statements for physical hazards

H280 Contains gas under pressure; may explode if heated.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008 [CLP]

Hazard pictograms



GHS04

Signal word
Warning

Hazard statements

H280 Contains gas under pressure; may explode if heated.

Precautionary statements

P403 Store in a well-ventilated place.

Supplemental hazard information

EIGA0357 Asphyxiant in high concentrations.
EIGA0787 Contains fluorinated greenhouse gases.
Please return container with residual pressure.
Withdrawal out of the liquid phase only.

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

2.3 Other hazards**Adverse human health effects and symptoms**

Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.
 The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.
 Contact with liquid may cause cold burns/frostbite.

Other adverse effects

The substance/mixture does not contain components identified as having endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated Regulation (EU) 2017/2100 or Commission Delegated Regulation (EU) 2018/605 in quantities of 0.1% or more.

Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

SECTION 3: Composition / information on ingredients**3.1 Substances**

not applicable

3.2 Mixtures**Hazardous ingredients**

CAS No	EC No	Index No	Substance name	Concentration	Classification according to Regulation (EC) No 1272/2008 [CLP]	SCL/ M/ ATE
811-97-2	212-377-0		1,1,1,2-Tetrafluoroethane (R 134a)	25.5 - 26.7 weight-%	Press. Gas (Liq.); H280	
354-33-6	206-557-8		Pentafluoroethane (R 125)	24.5 - 25.7 weight-%	Press. Gas (Liq.); H280	
754-12-1	468-710-7		2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	24.3 - 25.5 weight-%	Flam. Gas 1B; H221 Press. Gas (Liq.); H280	ATE(inhalation gas): > 405000 ppm
75-10-5	200-839-4		Difluoromethane (R 32)	23.3 - 24.5 weight-%	Flam. Gas 1B; H221 Press. Gas (Liq.); H280	

REACH No.	Substance name
01-2119459374-33	1,1,1,2-Tetrafluoroethane (R 134a)
01-2119485636-25	Pentafluoroethane (R 125)
01-0000019665-61	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)
01-2119471312-47	Difluoromethane (R 32)

Remark

The text of the H-and EUH-phrases is shown in section 16.

SECTION 4: First aid measures**4.1 Description of first aid measures****General information**

Remove contaminated, saturated clothing immediately.
 In the event of persistent symptoms obtain medical treatment.
 First aider: Pay attention to self-protection!

Following inhalation

Remove casualty to fresh air and keep warm and at rest.
 In case of respiratory arrest give artificial respiration by respiratory bag (Ambu bag) or respirator. Obtain medical assistance.

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

Following skin contact

In case of skin contact rinse with warm water.
In case of frostbite, wash with plenty of water; do not remove clothing.
In case of frostbite rinse with lukewarm (not hot) water for at least 15 minutes. Do not remove clothing frozen to the skin.
Thaw with lukewarm water. Apply a sterile dressing. Obtain medical assistance.

After eye contact

Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical assistance.

Following ingestion

Ingestion is not considered a potential route of exposure.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms

The following symptoms may occur in case of strong exposition:

Unconsciousness
Cardiac arrhythmias
Dizziness
Nausea
Headache

Effects

Long-term inhaling of separation products may cause pulmonary oedema.

4.3 Indication of any immediate medical attention and special treatment needed

Notes for the doctor

Treat symptomatically.
Do not apply drugs of the adrenaline ephedrine group.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

The product itself does not burn. The product itself does not burn. Match extinguishing measures to surrounding fire.
Extinguishing powder
alcohol resistant foam
Water spray jet

Unsuitable extinguishing media

Full water jet
Carbon dioxide (CO₂)

5.2 Special hazards arising from the substance or mixture

Hazardous combustion products

In case of fire formation of dangerous gases possible.
Carbon monoxide
Carbon dioxide (CO₂)
Hydrogen fluoride
Carbonyl fluoride

5.3 Advice for firefighters

Special protective equipment for firefighters

Wear a self-contained breathing apparatus and chemical protective clothing.

Additional information

If possible, shut off gas valves and move containers to a safe location.
Use water spray jet to protect personnel and to cool endangered containers.
Exposure to fire may cause rupture / explosion of the containers.
Dispose of fire residues and contaminated extinguishing water in accordance with local, official regulations.

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Use personal protection equipment.
Leave the danger area.
Keep people away and stay on the upwind side.

For emergency responders

Personal protection by wearing close-fitting protective clothing and breathing apparatus.
Pay attention to extension of gas especially at ground (heavier than air) and in direction of the wind.
Remove persons to safety.

6.2 Environmental precautions

If possible, stop flow of product.
Do not allow to enter into soil/subsoil.
Do not allow to enter into surface water or drains.

6.3 Methods and material for containment and cleaning up

For containment

If necessary, secure leaky pressure receptacles using a salvage container.
Prevent the liquid from spreading over a wide area (set up barriers, cover sewage systems).
Limit expansion of the gas (water spray jet).

For cleaning up

Leave to vapourize.
Provide adequate ventilation.

6.4 Reference to other sections

Disposal: see section 13
Personal protection equipment: see section 8

* SECTION 7: Handling and storage

7.1 Precautions for safe handling

Protective measures

Use only in well-ventilated areas.
Transfer and handle product only in closed systems.
Usual measures for fire prevention.
Containers' temperature should not be increased above 50 °C.
The working pressure in the receptacle must not exceed the saturation vapour pressure of the pure product resulting at a temperature of 50 °C.
Prevent cylinders from falling over.
Ensure valve protection device is correctly fitted.
Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
Open valve slowly to avoid pressure shock.
Do not allow backflow into the container.
Entering of water into the container must be prevented.
No water to valves, flanges and other fittings.
Purging of pipes and valves with inert gases - to avoid: water, solvents.

Advices on general occupational hygiene

When using do not eat, drink, smoke, sniff.
Wash hands before breaks and after work.
Remove contaminated clothing and protective equipment before entering eating areas.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

All regulations and local requirements for the storage of containers have to be respected.
Keep container tightly closed and in a well-ventilated place.
Containers' temperature should not be increased above 50 °C.
Prevent cylinders from falling over.
Only use containers specifically approved for the substance/product.
Information on suitable materials for receptacles and valves see ISO 11114.

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

Materials to avoid

Do not store together with explosives.
 Do not store together with flammable liquids.
 Do not store together with flammable solids.
 Do not store together with pyrophoric and self-heating substances.
 Do not store together with oxidizing liquids or oxidizing solids.
 Do not store together with toxic liquids or toxic solids.
 Do not store together with infectious substances.
 Do not store together with radioactive material.
 Do not store together with food or feed.

*** 7.3 Specific end use(s)**

* **Recommendation**
 An exposure scenario is not required.

*** SECTION 8: Exposure controls/personal protection***** 8.1 Control parameters***** DNEL worker**

CAS No	Substance name	DNEL value	DNEL type	Remark
354-33-6	Pentafluoroethane (R 125)	16444 mg/m ³	long-term inhalative (systemic)	Assessment factor 7.5, repeated dose toxicity.
75-10-5	Difluoromethane (R 32)	7035 mg/m ³	long-term inhalative (systemic)	Assessment factor 7.5
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	186400 mg/m ³	acute inhalative (systemic)	Assessment factor 5
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	950 mg/m ³	long-term inhalative (systemic)	
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	13936 mg/m ³	long-term inhalative (systemic)	Assessment factor 7.5, repeated dose toxicity.

*** DNEL Consumer**

CAS No	Substance name	DNEL value	DNEL type	Remark
354-33-6	Pentafluoroethane (R 125)	1753 mg/m ³	long-term inhalative (systemic)	Assessment factor 25, repeated dose toxicity.
75-10-5	Difluoromethane (R 32)	750 mg/m ³	long-term inhalative (systemic)	Assessment factor 25
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	186400 mg/m ³	acute inhalative (systemic)	Assessment factor 5
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	113.1 mg/m ³	long-term inhalative (systemic)	Assessment factor 2
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a)	2476 mg/m ³	long-term inhalative (systemic)	Assessment factor 15

*** PNEC**

CAS No	Substance name	PNEC Value	PNEC type	Remark
354-33-6	Pentafluoroethane (R 125)	0.1 mg/L	aquatic, freshwater	Assessment factor 1000
354-33-6	Pentafluoroethane (R 125)	1 mg/L	aquatic, intermittent release	Assessment factor 100
354-33-6	Pentafluoroethane (R 125)	0.6 mg/kg soil dw	sediment, freshwater	
75-10-5	Difluoromethane (R 32)	0.313 mg/L	aquatic, freshwater	Assessment factor 1000
75-10-5	Difluoromethane (R 32)	3.13 mg/L	aquatic, intermittent release	Assessment factor 100
75-10-5	Difluoromethane (R 32)	1.807 mg/kg dw	sediment, freshwater	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.1 mg/L	aquatic, freshwater	Assessment factor 1000
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1 mg/L	aquatic, intermittent release	Assessment factor 100
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.01 mg/L	aquatic, marine water	Assessment factor 10000

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

CAS No	Substance name	PNEC Value	PNEC type	Remark
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1.51 mg/kg dw	sediment, freshwater	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	0.151 mg/kg dw	sediment, marine water	
754-12-1	2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf)	1.49 mg/kg	soil	
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.1 mg/L		aquatic, freshwater	Assessment factor 1000
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 1 mg/L		aquatic, intermittent release	Assessment factor 100
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.01 mg/L		aquatic, marine water	Assessment factor 10000
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 0.75 mg/kg dw		sediment, freshwater	
811-97-2	1,1,1,2-Tetrafluoroethane (R 134a) 73 mg/L		sewage treatment plant (STP)	Assessment factor 10

8.2 Exposure controls**Appropriate engineering controls****Technical measures to prevent exposure**

Transfer and handle only in enclosed systems.

Personal protection equipment**Eye/face protection**

Protective goggles according to EN 166, in case of increased risk add protective face shield.

Hand protection

Safety gloves according to EN 388:

Chromate-free leather

Body protection:

Safety shoes with steel toecap.

Body covering work clothing or chemical resistant suit at increased risk.

Respiratory protection

Keep self contained breathing apparatus readily available for emergency use.

Respiratory protection necessary at:

high concentrations

Respiratory protection complying with EN 137.

Do not use any filter apparatus.

In case of rescue and maintenance activities in storage containers use environment-independent breathing apparatus because of risk of suffocation due to displacement of oxygen.

Thermal hazards

Use cold-resistant protective equipment.

Environmental exposure controls**Remark**

Prevent release to the environment.

SECTION 9: Physical and chemical properties**9.1 Information on basic physical and chemical properties****Physical state**

Gaseous / liquefied under pressure.

Colour

colourless

Odour

faintly of ether

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

Safety relevant basis data

	Value	Method	Source, Remark
Odour threshold:			not determined
Melting point/freezing point			not applicable
Boiling point or initial boiling point and boiling range	-46 °C pressure 1013 hPa		
flammability			none
Lower and upper explosion limit			none
Flash point			not applicable
Auto-ignition temperature			not determined
Decomposition temperature			No decomposition if used as directed.
pH			not applicable
Viscosity			not applicable
Solubility(ies)	Water solubility		not determined
Partition coefficient n-octanol/water (log value)			not applicable
Vapour pressure	12748 hPa (25°C)		
Density and/or relative density			not applicable
Relative vapour density	3.07 (25°C) pressure 1013 hPa		air = 1
particle characteristics			not applicable

9.2 Other information**Information with regard to physical hazard classes****Gases under pressure****Safety characteristics**

	Value	Method, Result	Source, Remark
Critical temperature	81.5 °C		

Other information

Vapours are heavier than air.

SECTION 10: Stability and reactivity**10.1 Reactivity**

The product is not flammable in air under ambient conditions of temperature and pressure. When pressurised with air, oxygen or other oxidants, it may become flammable.

10.2 Chemical stability

The mixture is chemically stable under recommended conditions of storage, use and temperature.

10.3 Possibility of hazardous reactions

Must not be mixed with air or oxygen.

Danger of fire and explosion with oxidants, alkali metals and earth alkali metals.

10.4 Conditions to avoid

Heat sources / heat - risk of bursting.

Ignition sources, open flames, glowing metal surfaces, etc.

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

10.5 Incompatible materials

Alkali metals
 Alkaline earth metal
 Powdered metals
 Oxidising agent, strong

10.6 Hazardous decomposition products

When handled and stored appropriately, no dangerous decomposition products are known.

SECTION 11: Toxicological information**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Animal data**

	Effective dose	Method, Evaluation	Source, Remark
Acute oral toxicity			Study technically not feasible.
Acute dermal toxicity			Study technically not feasible.
Acute inhalation toxicity	CAS No754-12-1 2,3,3,3-Tetrafluoroprop-1-ene (R 1234yf) Acute inhalation toxicity (gas) LC50: > 405000 ppm Species Rat Exposure time 4 h	OECD 403	

Other information

Based on available data, the classification criteria are not met.

Skin corrosion/irritation**Other information**

Study technically not feasible.

Serious eye damage/irritation**Other information**

Study technically not feasible.

Sensitisation to the respiratory tract**Other information**

No data available

Skin sensitisation**Other information**

Study technically not feasible.

Germ cell mutagenicity

	Value	Method	Result / Evaluation	Remark
In vitro mutagenicity/genotoxicity		OECD 473	negative	Information concerns main component.
In vivo mutagenicity/genotoxicity	Species Rat	OECD 486	negative	

Assessment/classification

Based on available data, the classification criteria are not met.

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

Carcinogenicity**Animal data**

	Value	Method	Result / Evaluation	Remark
Carcinogenicity	inhalative NOEL(C): 10000 ppm Species Rat Exposure duration 2 a	OECD 453		Information concerns main component.

Assessment/classification

Based on available data, the classification criteria are not met.

Reproductive toxicity**Animal data**

	Value	Method	Result / Evaluation	Remark
Reproductive toxicity	NOEL \geq 50000 ppm Species Mouse	OECD 478		Information concerns main component.

Assessment/classification

Based on available data, the classification criteria are not met.

STOT-single exposure**STOT SE 1 and 2****Assessment/classification**

Based on available data, the classification criteria are not met.

STOT-repeated exposure**Animal data**

	Effective dose	Method	Specific effects:	Organs affected:	Source, Remark
Inhalative specific target organ toxicity (repeated exposure)	NOAEL(C): 50000 ppm Species Rat Exposure duration 2 a	OECD 453			Information concerns main component.

Assessment/classification

Based on available data, the classification criteria are not met.

Aspiration hazard**Assessment/classification**

Study technically not feasible.

11.2 Information on other hazards**Additional information**

The inhalation of gas / vapour in high concentrations may cause cardiac arrhythmia.
 Inhalation causes narcotic effects/intoxication.

Other information

The product has not been tested. The information is derived from the properties of the individual components.

*** SECTION 12: Ecological information****12.1 Toxicity****Aquatic toxicity**

	Effective dose	Method, Evaluation	Source, Remark
Acute (short-term) fish toxicity	LC50: > 197 mg/L Species Cyprinus carpio (Common Carp) Test duration 96 h	OECD 203	R-1234yf

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

	Effective dose	Method, Evaluation	Source, Remark
Chronic (long-term) fish toxicity	not determined		
Acute (short-term) toxicity to crustacea	EC50 > 100 mg/L Species <i>Daphnia magna</i> (Big water flea) Test duration 48 h	OECD 202	R-1234yf
Chronic (long-term) toxicity to aquatic invertebrate	not determined		
Acute (short-term) toxicity to algae and cyanobacteria	EC50 142 mg/L Species Algae Test duration 96 h	QSAR	R-32
Chronic (long-term) toxicity to aquatic algae and cyanobacteria	not determined		
Toxicity to other aquatic plants/organisms	not determined		
Toxicity to microorganisms	EC10 730 mg/L Species growth of <i>Ps. putida</i> Test duration 6 h		R-134a

12.2 Persistence and degradability

	Value	Method	Source, Remark
Biodegradation	Degradation rate 5 % Test duration 28 d	OECD 301 D	CAS No75-10-5 Difluoromethane (R 32)
Biodegradation	Degradation rate < 5 % Test duration 28 d	OECD 301F/ ISO 9408/ EEC 92/69/V, C.4-D	CAS No754-12-1 2,3,3,3- Tetrafluoroprop-1-ene (R 1234yf)
Biodegradation	Degradation rate 5 % Test duration 28 d	OECD 301 D	CAS No354-33-6 Pentafluoroethane (R 125)
Biodegradation	Degradation rate 3 % Test duration 28 d	OECD 301 D	CAS No811-97-2 1,1,1,2- Tetrafluoroethane (R 134a)

Assessment/classification

Not readily biodegradable (according to OECD criteria)

12.3 Bioaccumulative potential**Assessment/classification**

Based on the n-octanol/water partition coefficients of the individual components of the mixture, accumulation in organisms is not expected.

12.4 Mobility in soil

	Value	Distribution	Transport type	Method	Remark
Half-life time in soil	CAS No811-97-2 1,1,1,2- Tetrafluoroethane (R 134a) 37.26 L/kg			KOC value	
Half-life time in soil	CAS No354-33-6 Pentafluoroethane (R 125) 20 L/kg			KOC value	
Half-life time in soil	CAS No75-10-5 Difluoromethane (R 32) 21.73 L/kg			KOC value	
Half-life time in soil	CAS No754-12-1 2,3,3,3- Tetrafluoroprop-1-ene (R 1234yf) < 18			KOC value	

R 449A

Print date 28.07.2025
 Revision date 28.07.2025
 Version 4.0 (en)
 replaces version of 22.03.2023 (3.0)

12.5 Results of PBT and vPvB assessment

The substance/mixture does not contain components meeting the PBT/vPvB criteria of the Reach Regulation, Annex XIII, at levels of 0.1% or higher.

*** 12.6 Endocrine disrupting properties**

No data available

*** 12.7 Other adverse effects**

	Value	Method	Source, Remark
Ozone depletion potential (ODP):	0		
Global warming potential (GWP)	1397		

Additional ecotoxicological information**Additional information**

The product has not been tested. The data are derived from the individual components of the mixture.

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Waste codes/waste designations according to EWC/AVV**

Waste code product	Waste name
140601 *	chlorofluorocarbons, HCFC, HFC

Appropriate disposal / Product

Waste disposal according to directive 2008/98/EC, covering waste and dangerous waste.
 Prevent release to the environment. No disposal via the sewage.
 Disposal according to local regulations.

Appropriate disposal / Package

Transportable pressure equipment (empty, residual pressure): Return to supplier / manufacturer.

SECTION 14: Transport information

	Land transport (ADR/RID)	Sea transport (IMDG)	Air transport (ICAO-TI / IATA-DGR)
14.1 UN number or ID number	UN 1078	UN 1078	UN 1078
14.2 UN proper shipping name	REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethan, Pentafluoroethan)	REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)	Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
14.3 Transport hazard class(es)	2.2	2.2	2.2
14.4 Packing group	-	-	-
14.5 Environmental hazards	No	No	No

14.6 Special precautions for user

The protective measures listed in Sections 6, 7 and 8 of the Safety Data Sheet have to be considered.

14.7 Maritime transport in bulk according to IMO instruments

No carriage in bulk.

Land transport (ADR/RID)

UN number or ID number	UN 1078
UN proper shipping name	REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethan, Pentafluoroethan)
Transport hazard class(es)	2.2
Hazard label(s)	2.2
Classification code	2A

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

Packing group	-
Environmental hazards	No
Limited quantity (LQ)	120 ml
Special provisions	274, 582, 662
Tunnel restriction code	C/E

Sea transport (IMDG)

UN number or ID number	UN 1078
UN proper shipping name	REFRIGERANT GAS, N.O.S. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
Transport hazard class(es)	2.2
Packing group	-
Environmental hazards	No
Limited quantity (LQ)	120 ml
Marine pollutant	No
EmS	F-C, S-V

Air transport (ICAO-TI / IATA-DGR)

UN number or ID number	UN 1078
UN proper shipping name	Refrigerant gas, n.o.s. (1,1,1,2-Tetrafluoroethane, Pentafluoroethane)
Transport hazard class(es)	2.2
Packing group	-
Environmental hazards	No

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture****EU legislation****Restrictions of occupation**

Observe employment restrictions under the Maternity Protection Directive (92/85/EEC) for expectant or nursing mothers.
Observe restrictions to employment for juvenils according to the 'juvenile work protection guideline' (94/33/EC).

Other regulations (EU)**To follow:**

Regulation (EU) 2024/573 on fluorinated greenhouse gases.
Regulation (EU) 2024/2174 laying down rules for the application of Regulation (EU) 2024/573 as regards the format of the labels for certain products and equipment containing fluorinated greenhouse gases.
Regulation (EU) 2024/2215 establishing, pursuant to Regulation (EU) 2024/573, ~ certification ~ as regards stationary refrigeration, air conditioning and heat pump equipment, and ~ containing fluorinated greenhouse gases.
National and local regulations concerning chemicals shall be observed.

Directive 2010/75/EU on industrial emissions [Industrial Emissions Directive] VOC
VOC-value ≥ 99 %

15.2 Chemical Safety Assessment**National regulations**

Chemical safety assessments for substances in this mixture were carried out.

R 449A

Print date 28.07.2025
Revision date 28.07.2025
Version 4.0 (en)
replaces version of 22.03.2023 (3.0)

SECTION 16: Other information

Key literature references and sources for data

Information from our suppliers and data from the "GESTIS Substances Database" and the "Registered Substances" database of the European Chemicals Agency (ECHA) were used to create this safety data sheet.

Classification for mixtures and used evaluation method according to regulation (EC) No 1272/2008 [CLP]

The mixture was classified by the manufacturer.

Additional information

The information contained herein is based on the state of our knowledge. It characterizes the product with regard to the appropriate safety precautions. It does not represent a guarantee of the properties of the product.

Relevant H- and EUH-phrases (Number and full text)

H221 Flammable gas.
H280 Contains gas under pressure; may explode if heated.

Indication of changes

* Data changed compared with the previous version